


Silicon Carbide Power MOSFET (N-Channel Enhancement)

V_{DS}	1700V
I_D (25°C)	8.3
$R_{DS(on)}$	500mΩ



Features

- High speed switching
- Essentially no switching losses
- Reduction of heat sink requirements
- Maximum working temperature at 175 °C
- High blocking voltage
- Fast Intrinsic diode with low recovery current
- High-frequency operation
- Halogen free, RoHS compliant

Typical Applications

Typical applications are in power factor correction(PFC), solar inverter, uninterruptible power supply, motor drives, photovoltaic inverter, electric car and charger.

Mechanical Data

- **Package:** TO-247AB
- **Terminals:** Tin plated leads
- **Polarity:** As marked

■Maximum Ratings (T_c=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE	TEST CONDITIONS	NOTE
Device marking code			D2170500NCTGH		
Drain source voltage @ T _j =25°C	$V_{DS,max}$	V	1700	$V_{GS}=0$ V, $I_D=100\mu$ A	
Gate source voltage @ T _j =25°C	$V_{GS,max}$	V	-10/+25	Absolute maximum values (AC f > 1Hz, duty cycle < 1%)	Note1
Gate source voltage @ T _j =25°C	$V_{GS,op}$	V	-5/+20	Recommended operational values	
Continuous drain current @ T _c =25°C	I_D	A	8.3	$V_{GS}=20$ V, T _c =25°C	Fig.14
Continuous drain current @ T _c =110°C			6	$V_{GS}=20$ V, T _c =110°C	
Pulse Drain Current	$I_{D,pulse}$	A	14.5	Limited by t _{pw}	Fig.15
Power Dissipation	P_{TOT}	W	89	T _c =25°C, T _j = 175°C	Fig.13
Operating junction and Storage temperature range	T _j , T _{stg}	°C	-55 to +175		
Soldering temperature	T _L	°C	260	1.6mm (0.063") from case for 10s	
Mounting torque	T _M	Nm	1.0	M3 screw Maximum of mounting process: 3	



■Static Electrical Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Gate threshold voltage	$V_{GS(th)}$	V	2	3.1	4.5	$V_{DS}=V_{GS}$, $I_D=1\text{mA}$	Fig.4, 11
Drain source breakdown voltage	$V_{(BR)DSS}$	V	1700			$V_{GS}=0$, $I_D=100\mu\text{A}$	
Zero gate voltage drain current	I_{DSS}	μA		<1	100	$V_{DS}=1700\text{V}$, $V_{GS}=0\text{V}$	
				5	500	$V_{DS}=1700\text{V}$, $V_{GS}=0\text{V}$, $T_j=175^\circ\text{C}$	
Gate source leakage current	I_{GSS}	nA			250	$V_{GS}=20\text{V}$, $V_{DS}=0\text{V}$	
Current drain source on-state resistance	$R_{DS(on)}$	$\text{m}\Omega$		480	650	$V_{GS}=20\text{V}$, $I_D=1.2\text{A}$	Fig.3, 5, 6
				960		$V_{GS}=20\text{V}$, $I_D=1.2\text{A}$, $T_j=175^\circ\text{C}$	
Transconductance	g_f	S		1.7		$V_{DS}=20\text{V}$, $I_D=1.2\text{A}$	

■Dynamic Electrical Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Input capacitance	C_{iss}	pF		714		$V_{DS}=1000\text{V}$, $V_{GS}=0\text{V}$, $T_j=25^\circ\text{C}$, $f=1\text{MHz}$, $V_{AC}=25\text{mV}$	Fig.10
Output capacitance	C_{oss}			21			
Reverse capacitance	C_{rss}			4			
Coss stored energy	E_{oss}	μJ		280		$V_{DS}=1000\text{V}$, $V_{GS}=0\text{V}$, $T_j=25^\circ\text{C}$, $f=1\text{MHz}$, $V_{AC}=25\text{mV}$	Fig.12
Gate source charge	Q_{gs}	nC		10.5		$V_{DS}=1000\text{V}$, $V_{GS}=-5/20\text{V}$, $I_D=1.2\text{A}$	Fig.16
Gate drain charge	Q_{gd}			8			
Gate charge	Q_g			30.5			
Internal Gate Resistance	$R_{G(int)}$	Ω		3.7		$f=1\text{MHz}$, $V_{AC}=25\text{mV}$	

■Switching Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Turn on delay time	$t_{d(on)}$	ns		13		$V_{DD}=1200\text{V}$, $V_{GS}=-4/+20\text{V}$, $I_D=1.2\text{A}$, $R_L=100\text{k}\Omega$, $R_{G(ext)}=2.7\Omega$	
Rise time	t_r			88			
Turn off delay time	$t_{d(off)}$			88			
Fall time	t_f			26.4			
Turn on switching energy	E_{on}	μJ		113		$V_{DD}=1200\text{V}$, $V_{GS}=0/+20\text{V}$, $I_D=1.2\text{A}$, $L=100\mu\text{H}$, $R_{G(ext)}=2.7\Omega$	Fig.17, 18
Turn off switching energy	E_{off}			4.2			



■Body diode characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Diode forward voltage	V _{SD}	V		6.2		V _{GS} =-5V, I _{SD} =3A	Fig.8
Continuous diode forward current	I _S	A		9.8		V _{GS} =-5V, Tc=25°C	
Reverse recovery time	t _{rr}	nS		36		V _{DS} =1200V, V _{GS} =-5V, I _{SD} =2A, di/dt=300A/uS	
Reverse recovery charge	Q _{rr}	nC		70			
Peak reverse recovery current	I _{rrm}	A		3.8			

Note 1: When using SiC Body Diode the maximum recommended V_{GS} = -5V

■Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Value
Thermal resistance	R _{θJ-C}	°C/W	1.69

■Typical Characteristics




Figure 1. Output Characteristics Tj = 25°C




Figure 2. Output Characteristics Tj = 175°C




Figure 3. On-resistance vs. drain current




Figure 4. Transfer Characteristics for various T_j




Figure 5. On-resistance vs. gate voltage for various T_j




Figure 6. On-resistance vs. Temperature for various Gate voltage




Figure 7. Normalized On-Resistance vs. Temperature




Figure 8. Reverse Output Characteristics at T_j = 25°C




Figure 9. Reverse Output Characteristics at Tj = 175°C




Figure 10. Capacitances vs. Drain to Source Voltage




Figure 11. Threshold voltage vs. temperature




Figure 12. Output Capacitor Stored Energy




Figure 13. Maximum Power Dissipation Derating vs. Case Temperature




Figure 14. Drain Current Derating vs. Case Temperature




Figure 15. Safe Operating Area




Figure 16. Gate Charge Characteristics




Figure 17. Clamped Inductive Switching Energy vs. Drain Current




Figure 18. Clamped Inductive Switching Energy vs. External Gate Resistor ($R_{G(ext.)}$)




Figure 19. Transient Junction to Case Thermal Impedance




Figure 20. Schematic of Resistive Switching





Figure 21. Switching Times Definition

Outline Dimensions



SYMBOL	DIMENSIONS			Note
	Min.	Typ.	Max.	
A	4.83	5.02	5.21	
A1	2.29	2.41	2.55	
A2	1.50	2.00	2.49	
b	1.12	1.20	1.33	
b1	1.12	1.20	1.28	
b2	1.91	2.00	2.39	6
b3	1.91	2.00	2.34	
b4	2.87	3.00	3.22	6, 8
b5	2.87	3.00	3.18	
c	0.55	0.60	0.69	6
c1	0.55	0.60	0.65	
D	20.80	20.95	21.10	4
D1	16.25	16.55	17.65	5
D2	0.51	1.19	1.35	
E	15.75	15.94	16.13	4
E1	13.46	14.02	14.16	5
E2	4.32	4.91	5.49	3
e	5.44 BSC			
L	19.81	20.07	20.32	
L1	4.10	4.19	4.40	6
φ P	3.56	3.61	3.65	7
φ P1	7.19 REF.			
Q	5.39	5.79	6.20	
S	6.04	6.17	6.30	

Note:

1. Package Reference: JEDEC TO247, Variation AD.
2. All Dimensions Are In mm.
3. Slot Required, Notch May Be Rounded
4. Dimension D & E Do Not Include Mold Flash. Mold Flash Shall Not Exceed 0.127mm Per Side. These Dimensions Are Measured At The Outermost Extreme Of The Plastic Body.
5. Thermal Pad Contour Optional Within Dimension D1 & E1.
6. Lead Finish Uncontrolled In L1.
7. φ P To Have A Maximum Draft Angle Of 1.5° To The Top Of The Part With A Maximum Hole Diameter Of 3.91mm.
8. Dimension "b2" And "b4" Does Not Include Dambar Protrusion. Allowable Dambar Protrusion Shall Be 0.10mm Total In Excess Of "b2" And "b4" Dimension At Maximum Material Condition.



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.